

**AMENDMENTS TO THE CLAIMS:**

This listing of claims will replace all prior versions, and listings, of claims in the application:

**Please amend the claims as follows:**

1. (Currently Amended) An outer mirror device for a vehicle comprising:  
a mirror for rearward viewing;  
a mirror surface angle adjusting mechanism mounted to the mirror, which receives power and adjusts a mirror surface angle of the mirror;  
a mirror surface angle detecting mechanism which can detect the mirror surface angle of the mirror;  
a control device electrically connected to the mirror surface angle adjusting mechanism and the mirror surface angle detecting mechanism, and supplying power to the mirror surface angle adjusting mechanism on the basis of an operation signal, and electrically ~~charging~~ changing the mirror surface angle detecting mechanism at appropriate times; and  
a mirror visor cover which accommodates the mirror surface angle adjusting mechanism, the mirror surface angle detecting mechanism and the control device between the mirror visor cover and the mirror, and  
a case containing said control device having a wall disposed between said mirror surface angle adjusting mechanism and said control mechanism.
2. (Withdrawn) An outer mirror device for a vehicle comprising:  
a mirror visor which covers a back surface of a mirror for rearward viewing to form a space between the mirror and the mirror visor;  
a mirror surface angle adjusting mechanism which has a first case and an electric motor accommodated in the first case, which is mounted to the mirror within the space, and which is able to adjust a mirror surface angle of the mirror by driving force of the electric motor;  
a control device having a second case disposed within the space, and a control substrate which is accommodated within the second case and at which is provided a control circuit supplying power to the electric motor on the basis of an operation signal;

a power supplying terminal provided at the control substrate and passing through the second case; and

a connector portion provided integrally with the second case, and fixed to the first case to connect the power supplying terminal to the electric motor.

3. (Withdrawn) The outer mirror device for a vehicle according to claim 2, wherein the mirror surface angle adjusting mechanism has a rotating member rotating due to rotation of the electric motor, and a drive rod which moves rectilinearly due to rotation of the rotating member and which changes the mirror surface angle of the mirror, and wherein

a mirror surface angle detecting sensor, which detects one of a position of the drive rod and a rotational position of the rotating member, is provided within the second case.

4. (Currently Amended) An outer mirror device for a vehicle comprising:  
a mirror visor cover which covers a back surface of a mirror for rearward viewing to form a space between the mirror and the mirror visor cover;

a mirror surface angle adjusting mechanism at which an electric motor, a rotating member rotating due to rotation of the electric motor, and a portion of a drive rod connected to the mirror and moving rectilinearly due to rotation of the rotating member, are accommodated in a first case, the mirror surface angle adjusting mechanism changing a mirror surface angle of the mirror by rectilinear movement of the drive rod;

a control device having a second case which is connected to the first case within the space, and a control substrate which is accommodated within the second case and at which is provided a control circuit power-supplying the electric motor on the basis of an operation signal; and

a mirror surface angle detecting sensor disposed within the second case, and detecting one of a position of the drive rod and a rotational position of the rotating member,

wherein one of said first and second cases includes a wall disposed between said mirror surface angle adjustment mechanism and said control device.

5. (Withdrawn) The outer mirror device for a vehicle of claim 3, wherein the mirror surface angle detecting sensor is provided at the control substrate.

6. (Original) The outer mirror device for a vehicle of claim 4, wherein the mirror surface angle detecting sensor is provided at the control substrate.

7. (Withdrawn) The outer mirror device for a vehicle of claim 5, wherein the mirror surface angle detecting sensor detects, in a non-contact manner, the one of the position of the drive rod and the rotational position of the rotating member.

8. (Withdrawn) The outer mirror device for a vehicle of claim 2, wherein the first case and the second case are integral.

9. (Original) The outer mirror device for a vehicle of claim 4, wherein the first case and the second case are integral.

10. (Currently Amended) The outer mirror device for a vehicle of claim 1, wherein the mirror surface angle adjusting mechanism has a first case, and the control device has a second case and the mirror surface angle detecting mechanism is provided in the second case, and said wall forms a portion of one of said first and second cases.

11. (Original) The outer mirror device for a vehicle of claim 10, wherein the first case and the second case are integral.

**Please add the following new claims:**

12. (New) The outer mirror device for a vehicle of claim 1, wherein said wall forms a portion of a case enclosing said control mechanism and said mirror surface angle detecting mechanism.

13. (New) The outer mirror device for a vehicle of claim 1, wherein said mirror surface angle adjusting mechanism includes a case having a frame wall that faces said first wall.

14. The outer mirror device for a vehicle of claim 1, wherein said first and frame walls are connected.

15. (New) The outer mirror device for a vehicle of claim 12, wherein said case enclosing said control mechanism and said mirror surface angle detecting mechanism is water tight.

16. (New) The outer mirror device for a vehicle of claim 4, wherein said second case is water-tight.

17. (New) The outer mirror device for a vehicle of claim 4, wherein said first and second cases include snap-fit connections for joining said cases together.

18. (New) The outer mirror device for a vehicle of claim 4, wherein said first case includes a frame wall that abuts said wall disposed between said control mechanism and said mirror surface angle adjustment mechanism.

19. (New) The outer mirror device for a vehicle of claim 1, wherein said wall includes an opening for accommodating an electrical connector for supplying an electrical current from said control mechanism to said mirror surface angle adjustment mechanism.

20. (New) The outer mirror device for a vehicle of claim 19, wherein said electrical connector includes detachably connectable electrical terminals.